

Photo	Model	Input	Output	Pulse Perido	Output Energy	Weight	Box Size	Unit Price (USD)
 The image shows a blue and white electric fence energizer, model TW-P3. It has a white faceplate with a green section at the bottom. The top of the faceplate has a blue handle. There are two buttons: 'Power' and 'Run/Alarm'. Below the buttons is a green section with a diagram of a fence and a cow. At the bottom, there are two terminals: a red one labeled '12KV+' and a black one labeled 'EARTH'. A 'DC12V IN' port is also visible. Two red and black cables are connected to the terminals.	TW-P3	DC12V2A	12KV	1.0S-1.5S(can be customized)	0.5-3J(can be customized)	0.9KG	23*21.7cm	\$26.90
 The image shows a blue and white electric fence energizer, model TW-P4. It has a white faceplate with a red LED display showing '11.8'. There are two buttons: 'Power' and 'Run/Alarm'. Below the buttons is a green section with a diagram of a fence and a cow. At the bottom, there are two terminals: a red one labeled '12KV+' and a black one labeled 'EARTH'. A 'DC12V IN' port is also visible. Two red and black cables are connected to the terminals.	TW-P4	DC12V2A	12KV	1.0S-1.5S(can be customized)	0.5-3J(can be customized)	0.92KG	23*21.7cm	\$29

 The image shows a blue plastic electric fence energizer, model TW-P5. It has a white faceplate with the text "ELECTRIC FENCE ENERGIZER" at the top. Below the text are two small circular indicators labeled "Power" and "Kunilarm". A green horizontal bar with five cow icons is positioned below the indicators. At the bottom of the faceplate, there are two red screw terminals and one black screw terminal. To the right of the energizer are two coiled cables: one red and one black, both with alligator clips at the ends.	TW-P5	DC12V2A	12KV	1.0S-1.5S(can be customized)	3J-7J(can be customized)	1.48KG	31.8*2 2cm	\$71.40
 The image shows a blue plastic electric fence energizer, model TW-P6. It has a white faceplate with the text "ELECTRIC FENCE ENERGIZER" at the top. Below the text is a small digital display screen. Under the screen are two green square buttons labeled "Power" and "Kunilarm". A green horizontal bar with five cow icons is positioned below the buttons. At the bottom of the faceplate, there are two red screw terminals and one black screw terminal. To the right of the energizer are two coiled cables: one red and one black, both with alligator clips at the ends. Below the cables is a small black and blue remote control with a silver keychain.	TW-P6	DC12V2A	12KV	1.0S-1.5S(can be customized)	3J-7J(can be customized)	1.56KG	31.8*2 2cm	\$79

	TW-5A	DX12V	8KV/12KV	0.75S-0.3S	1.5J	1.1KG	29*22*10.5cm	\$29
	TW-5	DX12V	8KV/12KV	0.75S-0.3S	2J	1.2KG	29*22*10.5cm	\$31.00



TW-10

DX12V

8KV/12KV

0.75S-0.3S

3J

1.25KG

29*22*
10.5cm

\$44.80



TW-20

DX12V

8KV/12KV

0.75S-0.3S

5J

1.3KG

29*22*
10.5cm

\$53.30

 The image shows an orange and grey electric fence energiser. The top orange section has the text "ELECTRIC FENCE ENERGISER" in bold. Below this, there are three terminals labeled "Ground Terre", "8KV", and "12KV", each with a lightning bolt icon. The bottom grey section has three terminals: a black one on the left and two red ones on the right.	TW-30	DX12V	8KV/12KV	0.75S-0.3S	7J	1.35KG	29*22*10.5cm	\$61.80
 The image shows an orange and grey electric fence energiser, similar to the one above but slightly larger. It has the same orange top with "ELECTRIC FENCE ENERGISER" text and "Ground Terre", "8KV", and "12KV" terminals. The bottom grey section also has three terminals: black on the left and two red on the right.	TW-40	DX12V	8KV/12KV	0.75S-0.3S	8J	1.40KG	29*22*10.5cm	\$70.30

 脉冲 电子围栏 智能 变频 5KM 7-13KV Electric leakage alarm Disconnection alarm Short circuit alarm power outage alarm 5KM/dual-screen pressure regulation/Alarm Model No.:MKF-5 Length Cable:5KM Alarm:Yes Adjust Voltage:7-13KV	MKF-5	DC12V	7-13KV	1-1.2S	2J	1.35KGS	30x26x10 cm	\$34.00
 脉冲 电子围栏 智能 变频 10KM 7-13KV Electric leakage alarm Disconnection alarm Short circuit alarm power outage alarm 10KM/Strong Type/Alarm Model No.:MKF-10 Length Cable:10KM Alarm:Yes Adjust Voltage:7-13KV	MKF-10	DC12V	7-13KV	1-1.2S	4J	1.35KGS	30x26x10 cm	\$48.00

 脉冲 电子围栏 智能 报警 20KM 7-13KV MKF-20 ✓ Electric leakage alarm ✓ Disconnection alarm ✓ Short circuit alarm ✓ power outage alarm 20KM/Strong Type/Alarm Model No.:MKF-20 Length Cable:20KM Alarm:Yes Adjust Voltage:7-13KV	MKF-20	DC12V	7-13KV	1-1.2S	6J	1.40KGS	30x26x10 cm	\$56.80
 脉冲 电子围栏 智能 报警 30KM 7-13KV MKF-30 ✓ Electric leakage alarm ✓ Disconnection alarm ✓ Short circuit alarm ✓ power outage alarm 30KM/Strong Type/Alarm Model No.:MKF-30 Length Cable:30KM Alarm:Yes Adjust Voltage:7-13KV	MKF-30	DC12V	7-13KV	1-1.2S	8J	1.45KGS	30x26x10 cm	\$65.60

 脉冲 电子围栏 智能 空断 报警 7-13KV 40KM Electric leakage alarm Disconnection alarm Short circuit alarm power outage alarm 40KM/Strong Type/Alarm Model No.:MKF-40 Length Cable:40KM Alarm:Yes Adjust Voltage:7-13KV	MKF-40	DC12V	7-13KV	1-1.2S	10J	1.50KGS	30x26x10 cm	\$73.80
10公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-01	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$76.00

20公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-02	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$88.60
30公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-03	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$102.30

40公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-04	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$110.80
50公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-05	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$121.90

60公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-06	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$132.90
70公里/劲霸型/可调节 智能开关 脉冲调节 电压调节: 8~15KV  主机 电瓶夹 输出线 电源适配器 报警器	TW-JB-07	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$141.50

	TW-JB-08	DC12V	8-15KV	0.3S-0.75S		1.50KGS	26*22*10 cm	\$153.40
	TW-X6	18-24VDC	1.5KV/3KV/5KV can be adjustable	Short circuit, disconnection		Pulse amplitude: high voltage 1500V-5000V, Pulse frequency: once every 1 second. Pulse duration: ≤ 0.1S	180mm*220mm*80mm	\$78.80

	TW-X5	18-24VDC	low voltage 900V-1500V, High voltage 3000V-5500V	Short circuit, disconnection, anti disassembly (some models have anti disassembly alarm function), power loss, Network contact (some models have network contact alarm function)		Pulse frequency: 1S-3S, adjustable Pulse duration : ≤ 0.1S, Peak value of pulse current: ≤ 10A Maximum electric quantity	345mm*265mm*95mm	Single zone:\$102.5, Dual Zone:\$119.8
	TW-X3	AC220V, DC12V	high voltage: 4KV-7.5KV; low voltage 0.6KV-1.5KV; the voltage is adjustable	Short circuit, disconnection		Pulse duration : ≤ 0.1S; pulse interval: 1.6S;	345mm*242mm*100mm	Single Zone:\$85.6; Dual Zone:\$93.8

